

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1(currently amended). A fork positioner for mounting upon a fork lift truck to selectively move respective forwardly-protruding load-lifting forks transversely, said fork positioner comprising:

(a) a first fork-engaging member slidably supported by a transversely extending first elongate moveable power actuator and a second fork-engaging member slidably supported by a transversely extending second elongate moveable power actuator, said first and second elongate moveable power actuators being transversely offset with respect to each other; and

(b) ~~actuation~~ movement of said first elongate power actuator causing said second fork-engaging member to slide transversely along said second elongate power actuator and ~~actuation~~ movement of said second elongate power actuator causing said first fork-engaging member to slide transversely along said first elongate power actuator.

2(previously presented). The fork positioner of claim 1 where said first and second elongate power actuators are hydraulic cylinders.

3(previously presented). The fork positioner of claim 1 where each said fork-engaging member has a base from which a pair of transversely-spaced legs depend to detachably engage a respective fork such that the base of said fork-engaging member is positioned above an upper portion of the respective fork and the legs of said fork-engaging member depend downwardly along transversely-opposite sides of the respective fork.

4(previously presented). The fork positioner of claim 3 where each said fork-engaging member has a fork-engaging position preventing said respective fork from being lifted upwardly off of a fork-supporting member, and a fork-disengaging position permitting said respective fork to be lifted upwardly off of said fork-supporting member.

5(previously presented). The fork positioner of claim 4 where each of said fork-engaging members is selectively movable on said fork positioner between said fork-engaging position and said fork-disengaging position.

Appl. No. 10/696,468

Amdt. dated February 21, 2005

Reply to Office action of November 22, 2004

6(currently amended). The fork positioner of claim 1 where ~~actuation~~ movement of said first and second elongate power actuators is synchronized to symmetrically adjust a transverse spacing between said fork-engaging members about an axis between said fork-engaging members.

7(currently amended). The fork positioner of claim 6 where said axis is transversely movable with respect to said lift truck.